Listing of Claims:

Claims 1 - 12 (Canceled).

13. (New) A printing apparatus for printing an image using a consumable detachably attached to the printing apparatus, wherein the consumable is adapted to output a response code obtained by encoding an identification code with a set logic and

5   wherein a first logic is set in the consumable as the set logic when the consumable is unused, said printing apparatus comprising:

a generating section which generates the identification code;

10 an output port which outputs the identification code to the consumable;

an input port through which the response code from the consumable is input;

an encoding section which encodes the identification code

15 using the first logic to obtain a first normal code;

a collating section which collates the first normal code with the response code input through the input port;

a change section which changes the set logic in the consumable to a second logic, which is different from the first

20 logic and which is determined in accordance with a predetermined

rule, when the response code coincides with the first normal
code;

a storage section which stores a plurality of said second
logics and a plurality of count values which are associated with
25   the second logics, respectively;

a storage control section which controls the storage
section;

an updating section which updates, in accordance with use of
the consumable, the count value stored in the storage section in
30   association with the second logic corresponding to the
consumable;

_____a determining section which determines whether each count
value is equal to or less than a limit value; and

an identifying section which identifies whether the
35   consumable is usable;

_____wherein if the response code coincides with the first normal
code, the change section changes the set logic to the second
logic determined in accordance with a predetermined rule, and the
storage control section causes the storage section to store the
40   determined second logic and an initial value as a count value,
and the identifying section identifies the consumable as usable;

wherein if the response code does not coincide with the
first normal code, the encoding section encodes the

identification code using each of the second logics stored in the

45   storage section to obtain second normal codes, and the collating

section collates the second normal codes with the response code;

wherein if the response code coincides with any one of the

second normal codes, the determining section determines whether

the count value associated with the second logic used by the

50   encoding section to obtain the coinciding second normal code is

equal to or less than the limit value, and the identifying

section identifies the consumable as usable if the count value is

equal to or less than the limit value, and identifies the

consumable as unusable if the count value is larger than the

55   limit value;

wherein if the response code does not coincide with the

first normal code and does not coincide with any said second

normal code, the identifying section identifies the consumable as

unusable.

14.   (New) The printing apparatus according to claim 13,

further comprising a parameter setting section which sets a

parameter commensurate with the count value corresponding to the

consumable, when the count value is equal to or less than the

limit value.

15.   (New) A method for controlling a printing apparatus for

printing an image using a consumable detachably attached to the

printing apparatus, wherein the consumable is adapted to output a

response code obtained by encoding an identification code with a

5   set logic and wherein a first logic is set in the consumable as

the set logic when the consumable is unused, said method

comprising:

generating the identification code;

outputting the identification code to the consumable;

10   receiving the response code from the consumable;

encoding the identification code using the first logic to

obtain a first normal code;

collating the first normal code with the received response

code;

15   if the response code coincides with the first normal code:

changing the set logic in the consumable to a second

logic, which is different from the first logic and which is

determined in accordance with a predetermined rule;

storing the determined second logic in a storage

20   section with stores a plurality of said second logics, each in

association with a corresponding count value, such that the

determined second logic is stored in association with a count

value that is an initial value;

identifying the consumable as usable; and

25   updating, in accordance with use of the consumable, the

count value stored in the storage section in association with the

determined second logic corresponding to the consumable; and

        if the response code does not coincide with the first normal

code:

30   encoding the identification code using one of the

plurality of second logics stored in the storage section to

obtain a second normal codes, and collating the second normal

code with the response code;

        repeating said encoding using a different one of the

35   stored second logics until one of: (i) one of the second codes

coincides with the response code, and (ii) it is determined that

none of the second codes coincide with the response code;

        when one of the second codes coincides with the

response code, determining whether the count value associated

40   with said one of the second codes is equal to or less than a

limit value, and identifying the consumable as (i) usable if the

count value is equal to or less than the limit value, and (ii)

unusable if the count value is larger than the limit value; and

        when none of the second codes coincide with the

45   response code, determining the consumable as unusable.

16.   (New) The method according to claim 15, further
comprising setting a parameter commensurate with the count value
corresponding to the consumable, when the count value is equal to
or smaller than the limit value.